

FORMPROFI ECO

TECHNICAL SPECIFICATION

Hourly capacity variable depending on the proofing time		
pieces/hour		4,000
Dimensions L x W x H (Cladding parts may protrude beyond the basic dimensions by 100 mm)		
mm		2,630 x 1,110 x 2,350
Minimum ceiling height		
mm		2,400
Variable pre-proofing time		
min.		9
Weight range		
g		40 - 65 / 75 depending on the stamping cups used
Proofing board dimensions		
mm		400 x 600 580 x 780 580 x 980
Pull-off length		
mm		1,000
Connected loads		
Electrical:	kW	4.5



FORMPROFI ECO
Compact form baking system with
integrated drum moule

WERNER & PFLEIDERER LEBENSMITTELTECHNIK GMBH
von-Raumer-Str. 8-18 // D-91550 Dinkelsbühl // Germany // Fon +49 9851-905-0 // Fax +49 9851-905-8342 //
info@wp-l.de // www.wp-l.de // www.wpbakerygroup.com

FORMPROFI ECO



WP CLEANTEC

- Hygiene concept



WP GREENENERGY

- Energy-efficient system operation



WP SMARTCONTROL

- Easy operation



WP BAKINGQUALITY

- Product-specific conditioning gentle on the dough



COMPACT FORM BAKING SYSTEM WITH INTEGRATED DRUM MOULDER FOR THE PRODUCTION OF

- KAISER ROLLS
- SMOOTH ROUND ROLLS
- AND OTHER FORMED ROLLS
- DOUBLE ROLLS

WITHIN A WEIGHT RANGE OF 40 TO 65/75 g (DEPENDING ON THE STAMPING CUPS USED)

BENEFITS

- Perfect craftsmanship quality
- Proven dividing principle of the Multimatic with integrated drum moulder
- Space saving – only 2.4 m ceiling height required
- Product diversity thanks to revolver stamping head with room for 1 fixed Kaiser dough stamp and 3 additional freely selectable and interchangeable dough stamps
- Perfect alignment thanks to separate stamping cups
- Use of commercially available proofing boards thanks to the variable depositing unit
- Siemens S7 touch screen control
- Optimum hygiene concept
 - Stainless steel design
 - Intense degermination
 - Ribbons removable for cleaning



SPECIFICATION

- 5-row system with 600 mm working width
- Integrated drum moulder with rotary valve
- Manual pressure adjustment
- Interchangeable moulding drum
- Adjustable moulding belt
- Revolver stamping head with 4 rows of tools max.
- Dough stamp for Kaiser rolls
- Manually adjustable flour duster
- Ribbon drying
- Maintenance-free ribbon chain with automatic tensioning
- Variable depositing unit for proofing boards in 3 Euro sizes, 400 x 600 / 580 x 780 / 580 x 980
- Proofing board fixture as a drawer
- Intensive degermination station
- Operator side left
- Siemens S7 touch screen control

OPTIONS

- Exhaust air ventilator for correction of the proofing cabinet climate with continuous operation
- Deposit unit with end position change
- Double-intensity degermination
- Laterally movable system variant
- Increased system height by 50 or 100 mm
- Collision protection on operator side
- Further chamber drums for variable weight ranges
- Stamping cups for different weight ranges
- Final proofing cabinet
- Stamping tools for
 - Star rolls
 - Button rolls
 - Rosette rolls
 - Pressed rolls
 - Kringel rolls
 - Kärntner rolls
 - Football rolls
 - Poppy seed rolls
 - Rhomb

